麦芽传感科技
Maiya Sensor Technology

MST 4 2 0

Portable Four-in-one Toxic And Harmful Gas Detector



Product introduction

Portable toxic and harmful gas detector can be used in: rapid detection of a variety of gas concentration and measurement of environmental temperature and humidity, if the measurement exceeded the limit value, the alarm will emit sound & light vibration as alarm. adopted 2.31-inch high-definition color screen for real-time display, adopted the gas sensors of industrially well-known brands, and the main detection principles include: electrochemical, infrared, catalytic combustion, thermal conductivity, PID photoionization, and so on. Advanced electric circuit design, mature kernel algorithm processing, unique external appearance design, had achieved a number of patents about the software works, external appearance, and so on. is suitable for detecting the concentrations of gases in the atmosphere environment in the pipeline or confined space; and the purity of the gas leakage and various high concentration single gases with the background gas as nitrogen gas or oxygen gas. The types of gases for detection are more than 500 types.

Features and benefits

- 1 ~ 4 kinds of gas can be detected at the same time (in kind), and the unit can be switched freely
- 3000mA high capacity rechargeable polymer battery is adopted, so it is possible to work for a long period of time.
- You can set whether to display the maximum value, minimum value, and average value
- Supports real-time detection or timed detection
- Rich man-machine interface
- English and Chinese interface is optional
- Large-capacity data storage (Larger capacity can be customized), supporting multiple storage modes
- A variety of alarm methods, when the alarm multi-directional three-dimensional indication alarm state
- Three display modes can be switched
- Protection grade up to IP65, waterproof splash, dustproof, explosion-proof, anti-vibration
- Graphical display, in the form of a curve to reflect the change trend of gas concentration in a period of time
- Multiple alarm mode Settings: low alarm, high alarm, interval alarm, TWA/STEL alarm
- Data recovery function, in case of misoperation can select partial or full recovery
- Standard USB charging interface, with charging protection function, support USB hot swap, charging state instrument can work normally
- Meet the design requirements of intrinsic safety circuit, anti -static, anti-electromagnetic radiation interference

Technical parameter

Gases to be detected	Arbitrary combination of 1 ~ 4 types of gases such as toxic gases, oxygen gas, carbon dioxide, inflammable and explosive gases, TVOC, and so on. Optional configuration: temperature and humidity measurements.
Application scenarios	All the cases which requires the portable rapid detection of gas concentrations such as petroleum, chemical, pharmaceutical, environmental protection, combustion gas distribution, warehousing, smoke gas analysis, air governance, and so on.
Detection range	0 ~ 1, 10, 100, 1000, 5000, 50000, 100000ppm, 200 mg/l, 100%LEL, 20%, 50%, 100%Vol can be selected; and other ranges can be customized.

Ningxia MaiYa Sensor Technology Development Co., LTD
E: maiyachuangan@163.com / 1255183250@qq.com

Resolution	0.01ppm or 0.001ppm (0 ~ 10 ppm); 0.01ppm (0 ~ 100 ppm), 0.1ppm (0 ~ 1000 ppm), 1ppm (0 ~ 1000 ppm or more), 0.01 mg/l (0 ~ 200% mg/l), 0.1% LEL, 0.01%Vol, 0.001% Vol				
Detection principle	Electrochemical, catalytic combustion, infrared, thermal conductivity, PID photoionization, and so on, depending on the type of gas, range, field environment and user demand.				
Sensor service life	Electrochemical principle: 2 ~ 3 years; Oxygen gas: 2 years or 6 years can be selected; infrared principle: 5 ~ 10 years; catalytic combustion: 3 years; thermal conductivity: 5 years; PID photoionization: 2 ~ 3 years.				
Maximum allowable error	≤±3% F.S (higher precision levels can be customized)				
Linearity	≤±2%	Linearity	≤±2%	Linearity	≤±2%
Response time	T90≤30 seconds			Recovery time	≤30 seconds
Working environment	Temperature: -40 ℃ ~ + 70 ℃, humidity: ≤10 ~ 95% RH				
Sample gas temperature	-40 ℃ ~ + 70 ℃, and the optional configuration of high-temperature sampling and cooling filter handle will be possible to detect the smoke gas at the temperature of 400 ℃ or higher.				
Temperature and humidity measurement	Optional configuration: temperature at -40 ℃ ~ + 70 ℃, accuracy level at 0.5 ℃; humidity at 0 ~ 100% RH, precision level at 3 % RH				
Power supply	3.7VDC、2100mAh high capacity rechargeable polymer battery				
Display mode	2.31-inch high-definition color screen				
Detection mode	Diffusion type measurement. The calibrated flow rate is 500 ml/minute.				
Alarm mode	It is possible to set as sound & light alarm, vibration alarm, sound & light + vibration alarm, turning off the alarm.				
Communication interface	USB (charging and communication), optional: RS485 communication interface				
Data storage	Standard configuration is the data storage capacity for 100, 000 entries				
Protection level	IP65				
Explosion-proof type	Intrinsically safe type				
Explosion-proof mark	Exia IIC T4 Ga				
Exterior dimensions	130×68×34mm (L×W×H)				
Weight	200 g				
Standard accessories	Manual, qualification certificate, warranty card, USB charger (including the data cable), belt clip, colorful packaging box (optional high-grade aluminum instrument case)				
Optional items	Temperature and humidity measurement function, external gas sampling pump, 1.2 m retractable sampling handle (1-10 meter hose, and the standard length is 1 meter), 0.4 meter stainless steel sampling handle (with dust filter, not retractable)				

Ningxia MaiYa Sensor Technology Development Co., LTD
E: maiyachuangan@163.com / 1255183250@qq.com

Part of gases specifications are as following:

Gases	Range	accuracy	resolution	response time	Principle
oxygen (O2)	0-30%/100%VOL	＜±3%(F.S)	0.1%VOL	<15s	EC
combustible gas (Ex)	0-100%LEL	＜ ±3%(F.S)	0.1%LEL	<10s	Catalytic Oxidation
	0-100%LEL/VOL	＜ ±3%(F.S)	0.1%LEL/VOL	<10s	NDIR
carbon oxide (CO)	0—1000/2000ppm	＜ ±3%(F.S)	0.1ppm	<25s	EC
hydrogen sulfide (H2S)	0-100/2000ppm	＜ ±3%(F.S)	0.1/1ppm	<30s	EC
sulfur dioxide (SO2)	0-100ppm	＜ ±3%(F.S)	0.1ppm	<30s	EC
Nitric Oxide (NO)	0-250ppm	＜ ±3%(F.S)	1ppm	<30s	EC
nitrogen dioxide (NO2)	0-20ppm	＜ ±3%(F.S)	0.1ppm	<60s	EC
Chlorine (Cl2)	0-20ppm	＜ ±3%(F.S)	0.1ppm	<30s	EC
Ammonia (NH3)	0-100ppm	＜ ±3%(F.S)	0.1/1ppm	<50s	EC
hydrogen (H2)	0-1000ppm	＜ ±3%(F.S)	1ppm	<60s	EC
hydrogen cyanide(HCN)	0-50ppm	＜ ±3%(F.S)	0.1ppm	<100s	EC
hydrogen chloride (HCl)	0-20ppm	＜ ±3%(F.S)	0.1ppm	<60s	EC
hydrogen phosphide(PH3)	0-20ppm/1000ppm	＜ ±3%(F.S)	0. 1ppm	<25s	EC
Ozone (O3)	0-20ppm	＜ ±3%(F.S)	0.01ppm	<30s	EC
chlorine dioxide (ClO2)	0-20ppm	＜ ±3%(F.S)	0.1ppm	<30s	EC
ethylene oxide (C2H4O,ETO)	0-100ppm	＜ ±3%(F.S)	0.1ppm	<45s	EC
Formaldehyde (CH20)	0-20ppm	＜ ±3%(F.S)	0.01ppm	<30s	EC
silane(SiH4)	0-50ppm	＜ ±3%(F.S)	0.1ppm	<60s	EC
hydrogen fluoride (HF)	0-10ppm	＜ ±3%(F.S)	0.1ppm	<60s	EC
fluorine (F2)	0-1ppm	＜ ±3%(F.S)	0.01ppm	<60s	EC
Phosgene (COCl2)	0-1ppm	＜ ±3%(F.S)	0.01ppm	<60s	EC
Total Volatile Organic Compound gases (TVOC)	0-10/100/2000ppm	＜±2%(F.S)	0.01/0.01/0.1ppm	<30s	EC
Total Volatile Organic Compound gases (TVOC)	0-10/100/2000ppm	＜±2%(F.S)	0.01/0.01/0.1ppm	<30s	PID

Note: please call us to consult about other gases and other detection range which are not listed in the above table.

Ningxia MaiYa Sensor Technology Development Co., LTD
E: maiyachuangan@163.com / 1255183250@qq.com